

**DATA SHEET FOR WEATHER PROOF ROTARY SWITCH****TECHNICAL DATA:**

PRODUCT	: CAT NO.- RI/105
PROTECTION	: WEATHER PROOF IP – 66 AS PER IS/IEC 60529:2001 (Reaffirmed 2014)
CERTIFICATION	: CIMFR
TEMP CLASS	: T6
MATERIAL	: DIE CAST ALUMINIUM ALLOY
FINISH	: EPOXY POWDER COATED SHADE AS PER IS : 5
EARTHING	: 1 No INTERNAL & 2 No's EXTERNAL
HARDWARE	: STAINLESS STEEL
GASKET	: 'O' RING ENDLESS GASKET NEOPRENE / SILICON
NAME PLATE	: SS NAME PLATE CUM WARNING PLATE
ENTRIES	: 2 NOS M20 / ½" NPT / EQUIVALENT
SWITCH	: UP TO 32 AMP TPN

**OPTIONS**

SR.NO	PARTICULAR	OPTIONS
1.	MATERIAL OF CONSTRUCTION	STAINLESS STEEL
2.	GLAND & PLUG	BRASS / SS / ALUMINIUM
3.	COLOUR SHADE	631, 632, 355, 7031, 7032 etc.
4.	CANOPY	M.S POWDER COATED / FRP / GI

SELECTION CHART

SR.NO	SWITCH RATING	POLE	VOLTAGE
1.	16 AMP	DP	240 V AC
2.	16 AMP	TP	415 V AC
3.	16 AMP	TPN	415 V AC
4.	20 AMP	DP	240 V AC
5.	20 AMP	TP	415 V AC
6.	20 AMP	TPN	415 V AC
7.	25 AMP	DP	240 V AC
8.	25 AMP	TP	415 V AC
9.	25 AMP	TPN	415 V AC
10.	32 AMP	DP	240 V AC
11.	32 AMP	TP	415 V AC
12.	32 AMP	TPN	415 V AC

