



DATA SHEET FOR FLP ROTARY SWITCH WITH TERMINATION CHAMBER

TECHNICAL DATA:

- PRODUCT : RI/OA/1010
- ENCLOSURE : FLAME PROOF (Ex -d), Gas Group IIA , IIB
As per IS/IEC 60079-1 : 2014
- PROTECTION : WEATHER PROOF IP – 66 AS PER IS/IEC 60529:2001
(Reaffirmed 2014)
- AREA & TEMP. CLASS : Ex db IIA,IIB T6 Gb (EX tb / tc IIIC T85 C Db/Dc
(ZONE 1 & 2 & Zone 21 & 22)
- CERTIFICATION : CIMFR, BIS, PESO
- TEMPERATURE CLASS : T6
- MATERIAL : DIE CAST ALUMINIUM ALLOY
- FINISH : EPOXY POWDER COATED SHADE AS PER IS : 5
- EARTHING : 1 No INTERNAL & 2 No's EXTERNAL
- HARDWARE : STAINLESS STEEL
- GASKET : 'O' RING ENDLESS GASKET NEOPRENE / SILICON
- NAME PLATE : SS NAME PLATE CUM WARNING PLATE
- ENTRIES : 2 NOS OF M20/ ½" NPT/ EQUIVALENT / UP TO M25
- SWITCH : UP TO 32 AMP
- TERMINALS : 4 NOS OF 2.5SQ.MM CLIP ON TYPE TERMINAL /
UPTO 6 SQ MM



OPTIONS

SR.NO	PARTICULAR	OPTIONS
1.	MATERIAL OF CONSTRUCTION	STAINLESS STEEL
2.	GLAND & PLUG	BRASS / SS / ALUMINIUM
3.	COLOUR SHADE	631, 632, 355, 7031, 7032 etc.
4.	CANOPY	M.S POWDER COATED / FRP / GI

SELECTION CHART

SR.NO	SWITCH RATING	POLE	VOLTAGE
1.	16 AMP	DP	240 V AC
2.	16 AMP	TP	415 V AC
3.	16 AMP	TPN	415 V AC
4.	20 AMP	DP	240 V AC
5.	20 AMP	TP	415 V AC
6.	20 AMP	TPN	415 V AC
7.	25 AMP	DP	240 V AC
8.	25 AMP	TP	415 V AC
9.	25 AMP	TPN	415 V AC
10.	32 AMP	DP	240 V AC
11.	32 AMP	TP	415 V AC
12.	32 AMP	TPN	415 V AC

