



DATA SHEET FOR FLP TELEPHONE

TECHNICAL DATA:

PRODUCT NAME	: CAT NO: TL / OA / 169
ENCLOSURE	: FLAME PROOF (Ex -d), Gas Group IIA , IIB As per IS/IEC 60079-1 : 2014
PROTECTION	: WEATHER PROOF IP – 66 AS PER IS/IEC 60529:2001 (Reaffirmed 2014)
AREA CLASSIFICATION	: Ex db IIA,IIB T6 Gb (EX tb / tc IIIC T85 C Db/Dc (ZONE 1 & 2 & Zone 21 & 22)
CERTIFICATION	: CIMFR, BIS, PESO
TEMPERATURE CLASS	: T 6
MATERIAL	: DIE CAST ALUMINIUM ALLOY
FINISH	: EPOXY POWDER COATED SHADE AS PER IS : 5
EARTHING	: 1 No INTERNAL & 2 No's EXTERNAL
HARDWARE	: STAINLESS STEEL
GASKET	: 'O' RING ENDLESS GASKET NEOPRENE / SILICON
NAME PLATE	: SS NAME PLATE CUM WARNING PLATE
ENTRIES	: 3 NOS AT BOTTOM OF M20 / ½" NPT / EQUIVALENT
VOLTAGE	: 48 V DC
SOUND LEVEL	: 100 dB AUDIBLE IN 1 METER WITH BUILT IN BUZZER
TERMINALS	: 6 NOS OF 15 AMP STRIP TYPE TERMINALS



SALIENT FEATURES :

- a) LED INDICATION FOR INCOMING CALLS
- b) METALLIC STAINLESS STEEL DIAL KEY PAD
- c) SS KEY PAD FLUSH BUTTON TYPE
- d) HAND SET ABS GLASS FILLED MATERIAL.
- e) STAINLESS STEEL FLEXIBLE CORD FOR HAND SET WIRE.
- f) PULSE / TONE (SELECTABLE)
- g) REDIAL FACILITY
- h) CIRCUIT WITH ZENIER BARRIER
- i) SILICON COATING ON KEY PAD TO PREVENT FROM DUST / MOISTURE / CHEMICAL.

OPTIONS

SR.NO	PARTICULAR	OPTIONS
1.	MATERIAL OF CONSTRUCTION	STAINLESS STEEL
2.	GLAND & PLUG	BRASS / SS / ALUMINIUM
3.	COLOUR SHADE	631, 632, 355, 7031, 7032 etc.
4.	HANSET	ALUMINIUM METAL
5.	CANOPY	M.S POWDER COATED / G.I / FRP

