



FRONT VIEW

SIDE VIEW

DOL/Star Delta Starter Selection Table for Electrical Components & Terminals :

MATERIAL	0.5 HP MOTOR	1 HP MOTOR	2 HP MOTOR	5 HP MOTOR	7.5 HP MOTOR	10 HP MOTOR	16 HP MOTOR
CONTRACTOR	1 No. 9 Amp.	1 No. 9 Amp.	1 No. 9 Amp.	1 No. 9 Amp.	1 No. 12 Amp.	1 No. 16 Amp.	1 No. 25 Amp.
O/L RELAY	1 No. 0.8-1.17 A	1 No. 1.6-2.3 A	1 No. 2.5-3.7 A	1 No. 6.3-9.4 A	1 No. 8-11.7 Amp	1 No. 12.5-18.7 A	1 No. 14-23 Amp.
ELEMENTS	2 Nos. 10 Amp.	2 Nos. 10 Amp.	2 Nos. 10 Amp.	2 Nos. 10 Amp.	2 Nos. 10 Amp.	2 Nos. 10 Amp.	2 Nos. 10 Amp.
TERMINALS	6 Nos. 2.5sq. mm	6 Nos. 2.5sq. mm	6 Nos. 2.5sq. mm	6 Nos. 2.5sq. mm	6 Nos. 2.5sq. mm	6 Nos. 4sq. mm	6 Nos. 2.5sq. mm
SWITCH	16 Amp.	16 Amp.	16 Amp.	16 Amp.	20 Amp.	25 Amp.	32 Amp.

Fitting OPTIONS :

- 1) MATERIAL CONSTRUCTION : STAINLESS STEEL
- 2) VOLTAGE : 230V / 415V AC
- 3) CABLE GLAND & PLUG : BRASS/S.S./ALUMINIUM
- 4) PAINT SHADE : 632/355/7031/7032, etc... (As per Standard)
- 5) CANOPY : M.S. / G.I. / FRP
- 6) CABLE ENTRIES : 2 Nos. M25 / 3/4" NPT / 1" ET

NOTE :
 COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING.
 OVERALL DIMENSIONS ARE ±10mm

REV.	DATE	DESCRIPTION	DRN.	CHD.	APPD.

- Reference IS/IEC Standard as follows :
- 1 - FLAMEPROOF (Ex d) PROTECTION - IIA/IIb, IS/IEC 60079-1 (2007)
 - TEMPERATURE CLASS - T6
 - 2 - INGRESS (IP) PROTECTION - IP-66, IS/IEC 60529 (2001).

Standard Specification :

- 1 - MATERIAL - CAST ALUMINIUM ALLOY
- 2 - FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING SHADE No. 631 AS PER IS-5
- 3 - EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS SCREWS WITH 2 Nos. PLAIN WASHER
- 4 - HARDWARE - STAINLESS STEEL
- 5 - GASKET - 'O' RING NEOPRENE RUBBER GASKET
- 6 - MOUNTING ARRGT. - AS SHOWN IN DRG.

Material / Components Specification :

- 1 - S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO, SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc...)
- 2 - SWITCH - 1 No. 6 Amp., 230V AC, SP/DP, ON-OFF SELECTOR SWITCH OF 'RECOM/KAYCEE/SULZER' MAKE
- 2 - ELEMENT - 2 Nos. 10 Amp., 415V AC, INO+INC CONTACT ELEMENT OF 'TEKNIK/VAISHNO' MAKE
- 3 - ACTUATOR - 1 No. GREEN COLOUR SPRING RETURN TYPE & 1 No. RED COLOUR MUSHROOM HEAD, PRESS & TURN TO 'STOP' & REVERSE TURN TO RELEASE TYPE ACTUATOR OF 'SUDHIR' MAKE
- (NECESSARY PAD LOCKING ARRGT. IN 'STOP' POSITION WITHOUT LOCK)
- 4 - CONTRACTOR - 1 No. OF 'L & T/SIEMENS/SCHNEIDER' MAKE (REFER TABLE RELAY - 1 No. OF 'L & T/SIEMENS/SCHNEIDER' MAKE (REFER TABLE)
- 5 - TERMINALS - 2.5sq. mm CLIP-ON TYPE TERMINALS OF 'ELMEX/CONNECTWELL' MAKE
- 6 - CABLE ENTRIES - 3 Nos. M20 / 1/2" NPT / 3/4" ET EQUIVALENT
- CABLE ENTRIES FROM BOTTOM SIDE - REFER DRAWING
- 7 - CABLE GLAND - (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF 'SUDHIR' MAKE
- 8 - STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE

CAT. No.	DOLS/OA/174	CAT. No.	SUDHIR SWITCHGEARS PVT. LTD.
MODEL No.	DOLS/174-9	130, MULBARI SAMAJHAR WARE, MULBARI - 400 023	
DRN.	profill		
CHD.	JASHWANTH		
APPD.			
SHEET	1 OF 1	CIMFR CERT. No.	
SCALE	N. T. S.	CIMFR/TC/SR/1431	PESO No. : PS24257/1
REV.-0		Dt. 24/01/2013	Dt. 02/03/2022
			BIS LICENCE No. : CM/L-0003331365

THIS DRAWING IS PROPERTY OF "SUDHIR SWITCHGEARS PVT. LTD." AND MUST BE RETURNED ON REQUEST IF IT IS SUBMITTED AS CONFIDENTIAL INFORMATION IN CONNECTION WITH ENQUIRY, TENDER, ORDER, OR CONTRACTS IT IS NOT TO BE USED FOR ANY OTHER PURPOSE OR ORDER NOR MAY IT RE-COPIED OR LENT WITHOUT OUR AUTHORITY IN WRITING.