This drawing is property of "**Sudhir Syttchgears** pyt. Ltd." and must be returned on request it is submitted as confidential information in connection with enquiry, tender, order, or contracts it is not to be used for any other purpose or order nor may it re-copied or lent without our authority in writing. FILE No. : DRAWING-2023/STD. G.A./JB/2017-2 5) 4 3) 2) Fitting OPTIONS: SENSOR CABLE GLAND & PLUG VOLTAGE MATERIAL CONSTRUCTION AMP. RATING PAINT SHADE CAPILLARY TUBE  $\bigoplus$ || || ١ \$ UPTO 10 Amp. (MAX.) 632/355/7031/7032, etc... (As per Standard) BRASS/S.S./ALUMINIUM 110V / 230V / 415V AC STAINLESS STEEL NAME PLATE (MOUNTING DIST.) WARNING PLATE CUM 130 162 FRONT VIEW CABLE ENTRY \_ ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED. 65 æv. (MOUNTING DIST.) 2 Nos. Ø 8mm MOUNTING HOLES COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS 20 120 OVERALL DIMENSIONS ARE ±10mm IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING. NOTE : DATE DESCRIPTION SIDE VIEW 8 DRN. SHS. APPO SCALE N. T. S. REV.- 0 CHKD. APPD. SHEET JB/2017-2 WODEL No.: JB/2C/2017 4 . . TEMPERATURE CLASS - T6 7 -6 5 I AKSHAY profull NPT / 3/4" ET SIZE - REFER DRAWING GASKET - '0' RING NEOPRENE RUBBER GASKET EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS FLAMEPROOF (Ex d) PROTECITON - IIA/IIB & IIC, IS/IEC 60079-1 (2014) STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE SUDHIR' MAKE CABLE GLAND - (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF CABLE ENTRIES - 2 Nos. BOTTOM SIDE CABLE ENTRIES OF M20 / 1/2" ELECTRONIC INSTRUMENT WILL BE PROVIDED INSIDE THE ENCLOSURE TO FIT ELECTRICAL / ROUND PLATE (BAKELITE / M.S. PLATE WITH EPOXY POWDER COATING) RANGE : 0-120°C OF 'ELCON' MAKE THERMOSTAT ELEMENT SWITCH RATING - 5 Amp. 230V AC, TEMP. INTERNAL SIZE OF ENCLOSURE (BODY+COVER) - ø100 x 55mm SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc....) S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO MOUNTING ARRGT. - AS SHOWN IN DRG HARDWARE - STAINLESS STEEL SHADE No. 631 AS PER IS:5 FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING MATERIAL - CAST ALUMINIUM ALLOY INGRESS (IP) PROTECITON - IP:66, IS/IEC 60529 (2001). (Reaffirmed 2014) Material / Components Specification: SCREWS WITH 2 Nos. PLAIN WASHER Reference IS/IEC Standard as follows Standard Specification: 유 Dt. 08/07/2022 CMRI. CERT. No THE FLAMEPROOF-WEATHERPROOF ENCLOSURE FOR IN/CIMFR/TR22/R/H136 SUDHIR SWITCHGEARS PVT. LTD. 130, MUNBAI SAMACHAR NARG, MUNBAI - 400 023 THERMOSTATIC ELEMENT CM/L-0003931365