THIS DRAWING IS PROPERTY OF "SUDHIR SWITCHGEARS PYT. LTD." AND MUST BE RETURNED ON REQUEST IT IS SUBMITED AS CONFIDENTIAIN INFORMATION IN CONNECTION WITH ENQUIRY, TENDER, ORDER, OR CONTRACTS IT IS NOT TO BE USED FOR ANY OTHER PURPOSE OR ORDER NOR MAY IT RE-COPIED OR LENT WITHOUT OUR AUTHORITY IN WRITING. FILE No. : DRAWING-2023/STD. G.A./RCP2022-SFU 5) 6) 4 3) 2) Fitting OPTIONS: MATERIAL CONSTRUCTION INTERNAL COMPONENTS PAINT SHADE CABLE GLAND & PLUG CABLE ENTRIES CANOPY VOLTAGE 385 385 0 0 ВЗ 8 Incoming / Outgoing Cable Entries NPT / EQUIVALENT ET THREADS UPTO 125 Amp. ISOLATOR / MCCB M.S. / G.I. / FRP 632/355/7031/7032, etc... (As per Standard) BRASS/S.S./ALUMINIUM STAINLESS STEEL Incoming / Outgoing Terminals FRONT VIEW (Bottom Side) SFU / MCCB 125 Amp. TPN 430 385 0 ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED. MOUNTING HOLES FOR ø13mm FREE COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS OVERALL DIMENSIONS ARE ±10mm IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING. NOTE : DATE SIDE VIEW 255 DESCRIPTION TERMINALS DRN. SHS. APPO SCALE N. T. S. REV.- 0 CHKD. APPD. RCP/2022/SFU-1 RCP/2C/2022 4 6 -AKSHAY TEMPERATURE CLASS - T6 EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE CABLE GLAND -CABLE ENTRIES - 2 Nos. M50 SIZE CABLE ENTRIES FROM BOTTOM SIDE CONNECTWELL' MAKE TERMINALS - 8 Nos. 70sq. mm BUSBAR TYPE TERMINALS OF 'ELMEX/ FUSE LINK SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc....) S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO MOUNTING ARRGT. - AS SHOWN IN DRG GASKET - 'O' RING NEOPRENE RUBBER GASKET HARDWARE - STAINLESS STEEL SHADE No. 631 AS PER IS:5 FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING MATERIAL - CAST ALUMINIUM ALLOY INGRESS (IP) PROTECITON - IP:66, IS/IEC 60529 (2001). (Reaffirmed 2014) FLAMEPROOF (Ex d) PROTECITON - IIA/IIB & IIC, IS/IEC 60079-1 (2014) 'SUDHIR' MAKE SFU - 1 No. 125 Amp. TP/TPN SWITCH FUSE UNIT WITH 125 Amp. SCREWS WITH 2 Nos. PLAIN WASHER Material / Components Specification: Reference IS/IEC Standard as follows Standard Specification: 유 Dt. 30/03/2022 THE FLAMEPROOF-WEATHERPROOF ENCLOSURE FOR IN/CIMFR/TR22/R/H549 CMRI. CERT. No. (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF SUDHIR SWITCHGEARS PVT. LTD 130, MUMBAI SAMACHAR MARG, MUMBAI - 400 023 CONTROL PANEL P541563/1 Dt. 23/07/2022 Page No.: CM/L-0003931365

103

THIS DRAWING IS PROPERTY OF "**Sudeir Syntchigears** pyt. Lyd." And Must be returned on request it is submitted as confidential information in connection with enquiry, tender, order, or contracts it is not to be used for any other purpose or order nor may it re-copied or lent without our authority in writing. FILE No. : DRAWING-2023/STD. G.A./RCP2022-SFU 5) 6) 4 3) 2) Fitting OPTIONS: MATERIAL CONSTRUCTION INTERNAL COMPONENTS PAINT SHADE CABLE GLAND & PLUG CABLE ENTRIES CANOPY VOLTAGE 385 480 Ф 0 Incoming / Outgoing Cable Entries NPT / EQUIVALENT 'ET' THREADS UPTO 250 Amp. ISOLATOR / MCCB M.S. / G.I. / FRP 632/355/7031/7032, etc... (As per Standard) BRASS/S.S./ALUMINIUM STAINLESS STEEL Incoming / Outgoing Terminals FRONT VIEW (Bottom Side) SFU / MCCB 250 Amp. TPN 430 440 385 480 ф. HOLES FOR ø13mm FREI ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED. MOUNTING COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS OVERALL DIMENSIONS ARE ±10mm IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING. NOTE : DATE SIDE VIEW 270mm DESCRIPTION TERMINALS 829 DRN. SHS. APPO SCALE N. T. S. REV.- 0 CHKD. APPD. SHEET RCP/2022/SFU-2 RCP/2C/2022 6 AKSHAY TEMPERATURE CLASS - T6 GASKET - '0' RING NEOPRENE RUBBER GASKET STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE CABLE GLAND -CABLE ENTRIES - 2 Nos. M63 SIZE CABLE ENTRIES FROM BOTTOM SIDE 'ELMEX/CONNECTWELL' MAKE TERMINALS - 8 Nos. 120-150sq. mm BUSBAR TYPE TERMINALS OF FUSE LINK SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc....) S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO MOUNTING ARRGT. - AS SHOWN IN DRG HARDWARE - STAINLESS STEEL EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING MATERIAL - CAST ALUMINIUM ALLOY INGRESS (IP) PROTECITON - IP:66, IS/IEC 60529 (2001). (Reaffirmed 2014) FLAMEPROOF (Ex d) PROTECITON - IIA/IIB & IIC, IS/IEC 60079-1 (2014) 'SUDHIR' MAKE SFU - 1 No. 250 Amp. TP/TPN SWITCH FUSE UNIT WITH 250 Amp. SCREWS WITH 2 Nos. PLAIN WASHER SHADE No. 631 AS PER IS:5 Material / Components Specification: Reference IS/IEC Standard as follows Standard Specification: 유 Dt. 30/03/2022 THE FLAMEPROOF-WEATHERPROOF ENCLOSURE FOR IN/CIMFR/TR22/R/H549 CMRI. CERT. No. (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF SUDHIR SWITCHGEARS PVT. LTD 130, MUMBAI SAMACHAR MARG, MUMBAI - 400 023 CONTROL PANEL P541563/1 Dt. 23/07/2022 Page No.: CM/L-0003931365

104