



FRONT VIEW

SIDE VIEW

- Fitting OPTIONS:**
- 1) MATERIAL CONSTRUCTION : STAINLESS STEEL
 - 2) VOLTAGE : 110V / 230V / 415V AC
 - 3) CABLE GLAND & PLUG : BRASS/S.S./ALUMINIUM
 - 4) PAINT SHADE : 652/355/7031/7032, etc... (As per Standard)
 - 5) CANOPY : M.S. / G.I. / FRP
 - 6) AMP. RATING : UPTO 32 Amp. (MAX.)
 - 7) MAKE OF SWITCH : KAYCEE/SULZER
 - 8) SWITCH RATING SELECTION :

Slr.	Switch Rating	Pole	Voltage	PN
1	16 Amp.	DP	240V AC	2P+E
2	16 Amp.	TP	415V AC	3P+E
3	16 Amp.	TPN	415V AC	4P+E
4	20 Amp.	DP	240V AC	2P+E
5	20 Amp.	TP	415V AC	3P+E
6	20 Amp.	TPN	415V AC	4P+E
7	25 Amp.	DP	240V AC	2P+E
8	25 Amp.	TP	415V AC	3P+E
9	25 Amp.	TPN	415V AC	4P+E
10	32 Amp.	DP	240V AC	2P+E
11	32 Amp.	TP	415V AC	3P+E
12	32 Amp.	TPN	415V AC	4P+E

THIS DRAWING IS PROPERTY OF "SUDHIR SWITCHGEARS PVT. LTD." AND MUST BE RETURNED ON REQUEST IF IT IS SUBMITTED AS CONFIDENTIAL INFORMATION IN CONNECTION WITH ENQUIRY, TENDER, ORDER, OR CONTRACTS IT IS NOT TO BE USED FOR ANY OTHER PURPOSE OR ORDER NOR MAY IT RE-COPIED OR LENT WITHOUT OUR AUTHORITY IN WRITING.

Reference IS/IEC Standard as follows :

- 1 - FLAMEPROOF (Ex d) PROTECTION - IIA/IIb, IS/IEC 60079-1 (2014)
- TEMPERATURE CLASS - T6
- 2 - INGRESS (IP) PROTECTION - IP-66, IS/IEC 60529 (2001). (Reaffirmed 2014)

Standard Specification :

- 1 - MATERIAL - CAST ALUMINIUM ALLOY
- 2 - FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING SHADE No. 631 AS PER IS-5
- 3 - EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS SCREWS WITH 2 Nos. PLAIN WASHER
- 4 - HARDWARE - STAINLESS STEEL
- 5 - GASKET - 'O' RING NEOPRENE RUBBER GASKET
- 6 - MOUNTING ARRGT. - AS SHOWN IN DRG.

Material / Components Specification :

- 1 - S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO, SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc...)
- 2 - SWITCH - 1 No. SELECTOR SWITCH OF 'RECOM' MAKE (REFER TABLE)
- 3 - RUBBER FLAP WILL BE PROVIDED (FOR SOCKET HOLDER)
- 4 - INTERLOCK ARRGT. SUCH AS THE PLUG CAN NOT BE REMOVED WHEN THE SWITCH IS IN 'ON' POSITION & CAN BE WITHDRAWN ONLY WHEN THE SWITCH IS IN 'OFF' POSITION.
- 5 - TERMINALS - 4 Nos. 2.5sq. mm CLIP-ON TYPE TERMINALS OF 'ELMEX/CONNECTWELL' MAKE
- 6 - CABLE ENTRIES - 2 Nos. BOTTOM SIDE & 1 No. PLUG TOP SIDE CABLE ENTRIES OF M20 / 1/2" NPT / 3/4" ET SIZE - REFER DRAWING
- 7 - CABLE GLAND - (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF 'SUDHIR' MAKE
- 8 - STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE

NOTE :
 COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING.
 OVERALL DIMENSIONS ARE ±10mm

REV.	DATE	DESCRIPTION	DRN.	CHD.	APPD.	SCALE	N. T. S.	REV.-0