This drawing is property of "**Sudhir Syttchgears** pyt. Ltd." and must be returned on request it is submitted as confidential information in connection with enquiry, tender, order, or contracts it is not to be used for any other purpose or order nor may it re-copied or lent without our authority in writing. FILE No. : DRAWING-2023/STD. G.A./RI105 6) 5) ∞ 4 3 2) Fitting OPTIONS: 120 CABLE GLAND & PLUG VOLTAGE MATERIAL CONSTRUCTION TYPE OF SWITCH AMP. RATING CANOPY PAINT SHADE MAKE OF SWITCH FRONT VIEW (M) Ő N XABLE ENTRIES (BOTTOM SIDE) FAN REGULATOR KAYCEE / SULZER / EQUIVALENT SINGLE POLE/ DOUBLE POLE/ TRIPLE POLE 10 Amp./ 16 Amp./ 20 Amp./ 25 Amp./ 32 Amp. M.S. / G.I. / FRP 632/355/7031/7032, etc... (As per Standard) BRASS/S.S./ALUMINIUM 110V / 230V / 415V AC STAINLESS STEEL 120 OFF 2 Nos. ø10mm MOUNTING HOLES ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED. æv. COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS OVERALL DIMENSIONS ARE ±10mm IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING. NOTE : KN0B **OPERATING** DATE DESCRIPTION SECTIONAL VIEW 120 SWITCH DRN. SHS. # APPO SCALE N. T. S. REV.- 0 MODEL No.: RI/105 CHKD. APPD. RI/105 SHEET O1 . . TEMPERATURE CLASS - T6 <u>-</u> AKSHAY SWITCH - 1 No. 6 Amp., 230V AC, SP/DP, ON-OFF SELECTOR SWITCH GASKET - '0' RING NEOPRENE RUBBER GASKET EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS FLAMEPROOF (Ex d) PROTECITON - IIA/IIB, IS/IEC 60079-1 (2014) CABLE ENTRIES FROM BOTTOM SIDE - REFER DRAWING CABLE ENTRIES - 2 Nos. M20 / 1/2" NPT / 3/4" ET EQUIVALENT STOPPING PLUG - (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE 'SUDHIR' MAKE CABLE GLAND - (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF OF 'RECOM' MAKE INTERNAL SIZE OF ENCLOSURE (BODY+COVER) - ø100 x 60mm SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc....) S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO MOUNTING ARRGT. - AS SHOWN IN DRG HARDWARE - STAINLESS STEEL SCREWS WITH 2 Nos. PLAIN WASHER SHADE No. 631 AS PER IS:5 FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING MATERIAL - CAST ALUMINIUM ALLOY INGRESS (IP) PROTECITON - IP:66, IS/IEC 60529 (2001). (Reaffirmed 2014) Material / Components Specification: Reference IS/IEC Standard as follows : Standard Specification: 유 Dt. 30/03/2022 CMRI. CERT. No THE: FLAMEPROOF-WEATHERPROOF ENCLOSURE FOR IN/CIMFR/TR22/R/H557 SUDHIR SWITCHGEARS PVT. LTD 130, MUNBAI SAMACHAR NARG, MUNBAI - 400 023 ROTARY ISOLATOR P538125/1 Dt. 11/07/2022 Page No.:

CM/L-0003931365

79